

AVANT[™] SERIES

SMOOTH • QUIET • CLEAN



COMING SOON



Smooth & Effortless
**PRECISION
BALL BEARING
SWIVEL**

QuikStart Wheel is
**QUIET &
ERGONOMICAL**

Sealed Bearings and
Components keep Avant
CLEAN & SAFE



AVANT SERIES

- Sealed precision ball bearings in swivel section and wheel for smooth and effortless mobility
- Total Lock Brake engages on wheel edges to maintain a smooth tread profile
- Quiet, non-marking QuikStart wheel
- Integrated thread guards for wheel protection and long life
- Maintenance-free construction
- Available in Stainless Steel, Conductive, and Antimicrobial options for infection control

Available In
**Stainless Steel,
Conductive and
Antimicrobial** options



Custom Colors
Available by Special Order

COMING SOON

AVANT

MedCaster

AVANT PLATE CASTERS		WHEEL DIAMETER	TREAD WIDTH	PLATE OVERALL SIZE	PLATE HOLE CENTERS	OFFSET	OVERALL HEIGHT	SWIVEL RADIUS	LOAD CAPACITY (kg)
SWIVEL		75	25	93.5 x 63.5	50 x 75	27		64.5	80
		100	32	93.5 x 63.5	74.5 x 44.5	36	146	86	100
		100	32	67 x 77	51.5/46.5 x 61.5/56	36	146	86	100
		125	32	93.5 x 63.5	74.5 x 44.5	40	169.5	102.5	100
		125	32	67 x 77	51.5/46.5 x 61.5/56	40	169.5	102.5	100
		150	32	93.5 x 63.5	74.5 x 44.5	45	195	120	100
		150	32	67 x 77	51.5/46.5 x 61.5/56	45	195	120	100
SWIVEL TOTAL LOCK		75	25	93.5 x 63.5	50 x 75	27		73	80
		100	32	93.5 x 63.5	74.5 x 44.5	36	146	102.5	100
		100	32	67 x 77	51.5/46.5 x 61.5/56	36	146	102.5	100
		125	32	93.5 x 63.5	74.5 x 44.5	40	169.5	102.5	100
		125	32	67 x 77	51.5/46.5 x 61.5/56	40	169.5	102.5	100
		150	32	93.5 x 63.5	74.5 x 44.5	45	195	120	100
		150	32	67 x 77	51.5/46.5 x 61.5/56	45	195	120	100
SWIVEL DIRECTIONAL LOCK		100	32	93.5 x 63.5	74.5 x 44.5	36	146	102.5	100
		100	32	67 x 77	51.5/46.5 x 61.5/56	36	146	102.5	100
		125	32	93.5 x 63.5	74.5 x 44.5	40	169.5	102.5	100
		125	32	67 x 77	51.5/46.5 x 61.5/56	40	169.5	102.5	100
		150	32	93.5 x 63.5	74.5 x 44.5	45	195	120	100
		150	32	67 x 77	51.5/46.5 x 61.5/56	45	195	120	100

AVANT BOLT HOLE CASTERS		WHEEL DIAMETER	TREAD WIDTH	BOLT HOLE	FASTENING TYPES	OFFSET	OVERALL HEIGHT	SWIVEL RADIUS	LOAD CAPACITY (kg)
SWIVEL		75	25		Threaded, Grip Ring, Round, Expanding Adapter, and More	27	103	64.5	80
		100	32	11		36	139	86	100
		100	32	13		36	139	86	100
		125	32	11		40	162	102.5	100
		125	32	13		40	162	102.5	100
		150	32	11		45	188	120	100
		150	32	13		45	188	120	100
SWIVEL TOTAL LOCK		75	25		Threaded, Grip Ring, Round, Expanding Adapter, and More	27	103	73	80
		100	32	11		36	139	102.5	100
		100	32	13		36	139	102.5	100
		125	32	11		40	162	102.5	100
		125	32	13		40	162	102.5	100
		150	32	11		45	188	120	100
		150	32	13		45	188	120	100
SWIVEL DIRECTIONAL LOCK		100	32	11	Threaded, Grip Ring, Round, Expanding Adapter, and More	36	139	102.5	100
		100	32	13		36	139	102.5	100
		125	32	11		40	162	102.5	100
		125	32	13		40	162	102.5	100
		150	32	11		45	188	120	100
		150	32	13		45	188	120	100

PLEASE CONTACT FACTORY FOR DETAILS

AVAILABLE THROUGH

MedCaster
 MedCaster.com

 +1 866 462 9700 (USA)

colson
 Colson-Castors.co.uk

 +44 121 556 7221 (UK)
 +31 318 536 611 (Holland)
 +48 61 8 666 762 (Poland)

RHOMBUS
 Rhombus-Castors.com

 +49 2192 9368 0 (Germany)
 +33 1 30 95 55 45 (France)